

# DOTTED®

Profili luminosi brevettati e Made in Italy  
Patented lighting profiles, Made in Italy

LUXALL®  
SHAPING YOUR LIGHT


Profili LED flessibili con luminosità puntiforme, realizzati in elastomero silconico co-estruso, termoisolante (Heatless) con circuiti e LED di alta qualità.

Il materiale silconico trasparente di protezione è flessibile e quindi facilmente adattabile a molte superfici, inoltre possiede una eccellente resistenza ai raggi solari (UV-IR) e agli agenti atmosferici. Dotted può essere tagliato e giuntato, seguendo le apposite istruzioni, nelle più svariate composizioni. Luce brillante, resistenza all'acqua, facilità di installazione, bassi consumi, lunga vita del sistema manutenzione quasi inesistente, sono le caratteristiche principali di questo innovativo prodotto.

LED flexible profiles with point brightness, realized in co-extruded silicone rubber with thermo-dissipating (Heatless) and LED circuits of high quality.

The transparent silicone protective material is flexible and therefore easy-fitting to many surfaces, moreover it has outstanding resistance to sunlight (UV-IR), weathering and atmospheric agents. Dotted can be cut and jointed, following the instructions, to make a vast array of compositions. Brilliant light, water resistance, easy installation, low consumption, long life, minimal maintenance, are the main features of this innovative product.

## DOTTED ROUND TOP LED SMD 3528 WHITE



**HEATLESS®**

### MONOCROMATICO / MONOCHROMATIC

LED/MT LED/MT	VOLT Vdc VOLT Vdc	TIPO LED TYPE OF LED	WATT/ MT WATT/ MT	FASCIO BEAM	COLORE LUCE LED** LED LIGHT COLOR**	UNITA' DI TAGLIO CUTTING UNIT	LUMEN/ MT LUMEN/ MT	LUMEN/ W LUMEN/ W
30LED/mt	24V*	TOP LED 3528 SUPER BRIGHTNESS	3,6W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	200mm (24V)  100mm (12V)	180 lm 200 lm 220 lm	50,00 lm 55,50 lm 61,1 lm
60LED/mt	24V*	TOP LED 3528 SUPER BRIGHTNESS	7,2W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	100mm (24V)  50mm (12V)	360 lm 380 lm 400 lm	50,00 lm 52,78 lm 55,58 lm
120LED/mt	24V*	TOP LED 3528 SUPER BRIGHTNESS	14,4W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	50mm (24V)  25mm (12V)	760 lm 800 lm 840 lm	52,78 lm 55,56 lm 58,33 lm

\*12V a richiesta - on request

**RGB (Rosso, Verde, Blu) / RGB (Red, Green, Blue)**

LED/MT LED/MT	VOLT Vdc VOLT Vdc	TIPO LED TYPE OF LED	WATT/ MT WATT/ MT	FASCIO BEAM	COLORE LUCE LED** LED LIGHT COLOR**	UNITA' DI TAGLIO CUTTING UNIT	LUMEN/ MT LUMEN/ MT	LUMEN/ W LUMEN/ W
120LED/mt	24V	TOP LED 3528 FULL COLOR	19,2W	120°	Rosso, Verde, Blu Red, Green, Blue	50 mm		

**DOTTED ROUND TOP  
LED SMD 5050 WHITE**

**MONOCROMATICO / MONOCHROMATIC**

LED/MT LED/MT	VOLT Vdc VOLT Vdc	TIPO LED TYPE OF LED	WATT/ MT WATT/ MT	FASCIO BEAM	COLORE LUCE LED** LED LIGHT COLOR**	UNITA' DI TAGLIO CUTTING UNIT	LUMEN/ MT LUMEN/ MT	LUMEN/ W LUMEN/ W
60LED/mt	24V*	TOP LED 5050	14,4W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	100mm (24V)  50mm (12V)	700 lm 750 lm 800 lm	48,61 lm 52,08 lm 55,55 lm

\*12V a richiesta – on request

**RGB (Rosso, Verde, Blu) / RGB (Red, Green, Blue)**

LED/MT LED/MT	VOLT Vdc VOLT Vdc	TIPO LED TYPE OF LED	WATT/ MT WATT/MT	FASCIO BEAM	COLORE LUCE LED** LED LIGHT COLOR**	UNITA' DI TAGLIO CUTTING UNIT	LUMEN/ MT LUMEN/ MT	LUMEN/ W LUMEN/ W
60LED/mt	24V	5050 FULL COLOR	14,4W	120°	Rosso, Verde, Blu Red, Green, Blue	50 mm		

**IP67\*\* – CLASS III**

\*\*escluse connessioni  
\*\*excluding connections



**ACCESSORI A RICHIESTA / ACCESSORIES ON REQUEST**



POWER SUPPLY



CONTROLLERS



CONNECTORS




CABLES



CAPS

**DOTTED SQUARE TOP**  
**LED SMD 3528 WHITE**



**HEATLESS®**

**MONOCROMATICO / MONOCHROMATIC**

LED/MT LED/MT	VOLT Vdc VOLT Vdc	TIPO LED TYPE OF LED	WATT/ MT WATT/ MT	FASCIO BEAM	COLORE LUCE LED** LED LIGHT COLOR**	UNITA' DI TAGLIO CUTTING UNIT	LUMEN/ MT LUMEN/ MT	LUMEN/ W LUMEN/ W
30LED/mt	24V*	TOP LED 3528 SUPER BRIGHTNESS	3,6W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	200mm (24V)	180 lm 200 lm	50,00 lm 55,50 lm
						100mm (12V)	220 lm	61,1 lm
60LED/mt	24V*	TOP LED 3528 SUPER BRIGHTNESS	7,2W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	100mm (24V)	360 lm 380 lm	50,00 lm 52,78 lm
						50mm (12V)	400 lm	55,58 lm
120LED/mt	24V*	TOP LED 3528 SUPER BRIGHTNESS	14,4W	120°	Bianco Caldo 3200K Bianco Neutro 4200K Bianco Freddo 5800K Warm White 3200K Neutral White 4200K Cold White 5800K	50mm (24V)	760 lm 800 lm	52,78 lm 55,56 lm
						25mm (12V)	840 lm	58,33 lm

\*12V a richiesta - on request

**RGB (Rosso, Verde, Blu) / RGB (Red, Green, Blue)**

LED/MT LED/MT	VOLT Vdc VOLT Vdc	TIPO LED TYPE OF LED	WATT/ MT WATT/ MT	FASCIO BEAM	COLORE LUCE LED** LED LIGHT COLOR**	UNITA' DI TAGLIO CUTTING UNIT	LUMEN/ MT LUMEN/ MT	LUMEN/ W LUMEN/ W
120LED/mt	24V	TOP LED 3528 FULL COLOR	19,2W	120°	Rosso, Verde, Blu Red, Green, Blue	50 mm		

IP67\*\* – CLASS III



\*\*escluse connessioni  
\*\*excluding connections

**ACCESSORI A RICHIESTA / ACCESSORIES ON REQUEST**



POWER SUPPLY



CONTROLLERS



CONNECTORS



CABLES



CAPS